

15A NCAC 02D .0516 SULFUR DIOXIDE EMISSIONS FROM COMBUSTION SOURCES

(a) Emissions of sulfur dioxide from any source of combustion, including air pollution control devices, discharged from any vent, stack, chimney, or flare shall not exceed 2.3 pounds of sulfur dioxide per million Btu input.

(b) When determining compliance with this standard:

- (1) the sulfur dioxide formed by the combustion of sulfur in fuels, wastes, ores, and other substances shall be included;
- (2) the sulfur dioxide formed or reduced as a result of treating flue gases with sulfur trioxide or other materials shall be included in the computation of emissions; and
- (3) the determination of Btu input shall not include the contribution from any portion of fuels used exclusively to inflate the heat input value used to demonstrate compliance with the emission standard in Paragraph (a) of this Rule.

(c) The standard set forth in Paragraph (a) of this Rule shall not apply to sulfur dioxide emission sources already subject to an emission standard for sulfur dioxide in 15A NCAC 02D .0524, .0527, .1110, .1111, .1206, or .1210.

*History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);
Eff. February 1, 1976;
Amended Eff. July 1, 2007; April 1, 2003; July 1, 1996; February 1, 1995; October 1, 1989;
January 1, 1985; April 1, 1977;
Readopted Eff. November 1, 2020;
Amended Eff. June 1, 2023.*